

DURACO® HIGH BOND White 0.010

Material Description: Duraco® High Bond 24 utilizes multi purpose acrylic adhesive on both sides of firm foam. The adhesive provides excellent adhesion to a wide range of high and medium surface energy substrates including metal, glass and different types of plastics. The foam core provides good contact to applied surface. Replaces rivets, welds, and mechanical fasteners. Duraco® High Bond 24 is ideal for interior and exterior use with its good resistance to temperature cycles and moisture.



Product Information	Description
Product Color	White
Adhesive	General Purpose Acrylic
Carrier	Acrylic Foam
Application Temperature (°F)	70 to 100
Service Temperature (°F)	-20 to 200
Thickness (inch)	0.010

DHB	Typical Properties	Test Method
90° Peel Adhesion (lb/in):	12	ASTM D3330
Normal Tensile - T-Block (lb/0.5in ²)	100	ASTM D897
Dynamic Shear (lb/0.5in ²):	100	ASTM D1002
Static Shear (minutes)		
1.0 in ² , 72°F, 10lb load	20	ASTM D3654
Static Shear (minutes)		
1.0 in ² , 150°F, 500 gram load	20	ASTM D3654

*Tests are performed on 2 mil PET

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.