

## MAGNETIC TAPE - Indoor

**Material Description:** Duraco Magnetic Tape Indoor has a flexible magnetic material coated with a high tack rubber based adhesive on one side. Available in two thicknesses for wide application needs: 0.030" for lightweight applications, graphics, packet attachment, calendars and 0.060" for lightweight plastics, banners, appliance signage, nameplates and advertising signs. Available in continuous rolls or cut pieces.



Product Information	Description	
Material:	Standard Energy Flexible Magnetic Strip	
Adhesive	Rubber Based	
Release Liner	Silicone Coated Paper	
Application Temperature (°F)	65 to 100	
Service Temperature (°F)	-20 to 175	
Magnet Thickness:	.030" and .060"	

  

Adhesive	Typical Value	Test Method
Shear Resistance (hrs) 1 in <sup>2</sup> , 72°F (min) 1kg Load:	300.0	PSTC-107
180° Peel (lb/in):	8.0	PSTC-101
Loop Tack (lb/in):	10.0	PSTC-16

\*Tests are performed on 2 mil PET

### Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.