



HKC91 Technical Data Sheet

Double Coated Tape

A Double Coated (High/Low) Tape with a resealable adhesive on one side and an aggressive permanent adhesive on the other. Supported with polyester carrier with a White BOPP release liner

Product Features

- Excellent Resealable Adhesive System With Easy Smooth Release From Film Surfaces
- Centered Adhesive Provides A Finger Lift Edge From Either Side Of The Tape
- Available in TDE (True Dry Edge) Construction
- Clear, Printed Release Liner Available

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Width Exposed Side
Release Liner	1/2" (12mm)	1/4" (6mm)	1/2" (12mm)
1.8mil (45u) White Polypropylene (BOPP) Film	3/4" (19mm)	1/2" (12mm)	3/4" (19mm)
Adhesive	1" (25mm)	3/4" (19mm)	1" (25mm)
Rubber Based Hot Melt Adhesive	Available Widths	Adhesive Thickness	Adhesive Thickness
Liner Side Adhesion *	1/2" (12mm)	1.5mils	1.0mils
21 oz./in	3/4" (19mm)	1.5mils	1.0mils
Exposed Side Adhesion *	1" (25mm)	1.5mils	1.0mils
71 oz./in	Diameter	Weight	Weight per Case
Carrier	1/2" (12mm) - 16	3.0#/roll (1.0Kg)	37# (16.7Kg)
0.48 mil (12u) Clear Polyester	3/4" (19mm) - 16	6.5#/roll (2.0Kg)	53# (24.1Kg)
* Above Reflect Typical Values	1" (25mm) - 16	9.0#/roll (4.0Kg)	55# (25.0Kg)
Notes:	Flat Rolls Per Case	Spools Per Case	Cases per Skid (Cases / Spools)
• Low Slip Or No Slip Films Are Highly Recommended	1/2" x 3,000' (915m) - 12	1/2" x 21,000' (6,400m) - 1	24 / 45
• Corona Treatment On Film Surfaces Improves Adhesion Properties	3/4" x 3,000' (915m) - 8	3/4" x 15,000' (4,572m) - 1	24 / 45
• Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105	1" x 3,000' (915m) - 6	1" x 12,000' (3,658m) - 1	24 / 45