



## HIGH DENSITY URETHANE (PORON®) Superb compression resistance

A open cell foam that exhibits closed cell characteristics when compressed. It offers very low compression set, good shock absorption, and low out-gassing. Available in rubber-based or acrylic-based.



### FEATURES:

- Very low compression set
- Good shock absorption
- Low out-gassing
- Ideal for open/close gasket applications

### APPLICATIONS:

- Electrical enclosures
- Access doors/panels
- Louver and vent gasketing
- Lighting
- HVAC enclosures
- Electronics

### SPECIFICATIONS:

- Test Method: ASTM D3574
- Density (lb/ft<sup>3</sup>): 15
- Compression Deflection: 4 to 8 psi
- Compression Set (50%): 10 max
- Service Temperature: Rubber-based: -20°F to 150°F;  
Acrylic-based: -20°F to 190°F
- Flammability: FMVSS 302 UL94 HBF ≥ 3/16"

Can't find your size?  
**We customize.**

Try more  
of our  
weather stripping  
+ gasketing  
products!

**STANDARD ROLLS**

*3" diameter core*

Part Number	Thickness	Width	Length	Adhesive	Rolls/Carton
	in	in	ft		
472076	1/8	1/2	50	Acrylic	20
472078	1/8	1	50	Acrylic	10
472079	1/4	1/2	50	Acrylic	20
472081	1/4	1	50	Acrylic	10
472084	1/2	1	25	Acrylic	10
472085	1/8	1/2	50	Rubber	20
472087	1/8	1	50	Rubber	10
472088	1/4	1/2	50	Rubber	20
472089	1/4	3/4	50	Rubber	13
472090	1/4	1	50	Rubber	10
472091	1/2	1/2	25	Rubber	20
472093	1/2	1	25	Rubber	10

*\*Roll diameter listed is nominal with a tolerance of +/- 6%.*

**NEED QUICK TURNAROUND?**

Duraco manufactures and converts in-house, providing the convenient service of fast shipping and on-site tape experts. Contact us today.



**LET'S TALK**