



PT774 Technical Data Sheet

Transfer Tape

High Performance Permanent
Unsupported Adhesive Transfer Tape with
Tinted Blue Polyester Release Liner

Product Features

- More Aggressive Than PT777 Having Superior Bonding Properties for Heavier Walled Plastic Bags, Envelopes and Some Corrugated Boxes and Card Stock
- Will Tear or Distort Films >3 Mils in Thickness
- Liner is Hot Knife Cuttable

	Overall Liner Widths Available	Adhesive Width Liner Side	Adhesive Thickness
Release Liner	1/2" (12mm)	5/16" (8mm)	4.0 mil
1.42 mil Polyester Film Tinted Blue	3/4" (19mm)	1/2" (12mm)	4.0 mil
Adhesive	1" (25mm)	3/4" (19mm)	4.0 mil
Rubber Based Hot Melt Adhesive	Diameter	Weight	Weight per Case
Adhesion *	1/2"(12mm) - 15	3.0#/roll (1.4Kg)	37#(16.8Kg)
143 oz./in	3/4" (19mm) - 15	4.5#/roll (2.0Kg)	37#(16.8Kg)
	1" (25mm) - 15	6.0#/roll (2.7Kg)	37#(16.8Kg)
	Flat Rolls Per Case	Cases per Skid	
	1/2" x 3,000' (914m) - 12	24	
	3/4" x 3,000' (914m) - 8	24	
	1' x 3,000' (914m) - 6	24	

* Above Reflect Typical Values

Notes:

- Low Slip Or No Slip Films Are Highly Recommended
- Corona Treatment On Film Surfaces Improves Adhesion Properties
- Adhesives Are Compliant With FDA Regulations For Indirect Food Contact - CFR 175.105